

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in this application:

1 - 11. (Canceled)

12. (Currently amended) An integrated pin and clip comprising:

a shaft member;

a locking member movable between a first position and a second position, wherein said first position allows for insertion and removal of the integrated pin and clip into a receiving hole and said second position does not allow for insertion and removal of the integrated pin and clip into a receiving hole; and

retention means that secures said locking member in either one of said first position and said second position,

wherein the shaft member includes at least one cut-out portion disposed along a slot in the shaft member on an outer surface and sized to receive the locking member in seating engagement ~~and retain the locking member in the second position, such that pivoting of the locking member out of the second position is prohibited while the locking member is in seating engagement with the at least one cut-out portion.~~

13. (Original) The integrated pin and clip of claim 12 further comprising an angled end portion located at a second end of said shaft member.

14 - 17. (Canceled)

18. (Original) The integrated pin and clip of claim 12 further comprising a set of nubs located on said shaft member.

19 - 23. (Canceled)

24. (Previously Presented) The integrated pin and clip of claim 12, wherein the shaft member includes first and second cut-out portions disposed approximately 90° apart from each other.

25. (Canceled)

26. (Previously presented) The integrated pin and clip of claim 12, wherein the locking member is adapted to be pulled out of engagement with the at least one cut-out to allow the locking member to be rotated from the second position to the first position.

27 - 29. (Canceled)

30. (Currently Amended) An integrated pin and clip comprising:

a shaft member;

a locking member located at a first end of said shaft member, wherein said locking member is movable between a first position that is generally coaxial to said shaft member and a second position in which the locking member extends laterally from only one side of said shaft member; and

retention means that secures said locking member in either one of said first position and said second position;

wherein the shaft member includes at least one cut-out portion on an outer surface sized to receive the locking member in seating engagement ~~and retain the locking member in the second position,~~ such that pivoting of the locking member out of the second position is prohibited while the locking member is in seating engagement with the at least one cut-out portion.

31. (Previously presented) The integrated pin and clip of claim 30, wherein the locking member is adapted to be pulled out of engagement with the at least one cut-out to allow the locking member to be rotated from the second position to the first position.

32. (New) The integrated pin and clip of claim 12, wherein the locking member is adapted to be axially pulled away from the shaft and out of engagement with the at least one cut-out to allow the locking member to be rotated from the second position to the first position.

33. (New) The integrated pin and clip of claim 30, wherein the locking member is adapted to be axially pulled away from the shaft and out of engagement with the at least one cut-out to allow the locking member to be rotated from the second position to the first position.

34. (New) An integrated pin and clip comprising:

a shaft member;

a locking member pivotable between a first position and a second position, wherein said first position allows for insertion and removal of the integrated pin and clip into a receiving hole and said second position does not allow for insertion and removal of the integrated pin and clip into a receiving hole; and

retention means that secures said locking member in an engaged condition when the locking member is in the second position, such that pivoting of the locking member out of the second position is prohibited while the locking member is in the engaged condition;

wherein the locking member is configured to be axially pulled away from the shaft and out of the engaged condition to allow the locking member to be pivoted from the second position to the first position.

35. (New) The integrated pin and clip of claim 34, wherein when the locking member is in the engaged condition, a portion of the locking member is received in seating engagement with a cut-out portion of the shaft.